

# Wall Mount Switching Adapter SSA-1201 Single Output Series



www.seasonic.com



### Applications:

- Mini ITX system
- POS
- DVR
- Printer
- Panel pc
- KIOSK
- POE
- Desktop

### Features:

- Universal input
- Japanese Capacitor
- High efficiency 87%
- Meet CEC Level V, ErP Lot 7, Energy Star EPS2.0
- Over voltage protection
- Over current protection
- Short circuit protection
- Over Thermal protection
- No load consumption  $\leq 0.5W$

### Output Specifications:

Model	Output power	Min. Load	Max. Load	Total power	Efficiency
SSA-1201-12	12V	0A	8.5A	102W	87%
SSA-1201-19	19V	0A	6.32	120W	87%
SSA-1201-24	24V	0A	5	120W	87%
SSA-1201-48	48V	0A	2.5A	120W	87%
SSA-1201-50	50V	0A	2.4A	120W	87%

### General Specifications:

- Input voltage range: 90~264 Vac
- Input frequency: 47~63 Hz
- Input current: 2A (rms)
- Efficiency:  $\geq 87%$  Average
- Leakage current: 3.5mAa max.

**Safety:** CB, TUV, CCC, PSE, BSMI, cTUVus, KC, CEC, C-tick

**EMC:** CE, FCC

### Dimension:

L174 × W65 × H37 mm

(L6.85 × W2.56 × H1.46 inch)

Sea Sonic Electronics Co., Ltd.

www.seasonic.com  
sales@seasonic.com.tw  
Tel: +886 2 2659 0338  
Fax: +886 2 2659 0530

Seasonic Electronics Inc.

www.seasonicusa.com  
usa@seasonic.com  
Tel: +1 626 969 9966  
Fax: +1 626 969 9986

Sea Sonic Europe B.V.

europe@seasonic.com  
Tel: +31 (0)10-2262131  
Fax: +31 (0)10-2519947

